



RECOMMENDED PCB LAYOUT(L=0.80±0.05)
COMPONENT SIDE(GENERAL TOLERANCE:±0.05)

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

REV	DESCRIPTION	DATE	APPROVED
A	新板发行	2020. 11. 06	HHM

NOTES:

SPECIFICATION:

1. CURRENT RATING: 3.0A MAX
2. VOLTAGE: 100 VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. LNSERTION FORCE : 5N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY: 10,000 CYCLES

5	COVER	HIGH TEMPERATURE PLASTIC	LCP BLACK	1PCS
4	SPRING	STAINLESS STEEL	---	2PCS
3	LATCH	STAINLESS STEEL	TIN:80~120u"Min/Ni base:50u"Min Plated	1PCS
2	SHELL	STAINLESS STEEL	Ni:50u"Min Plated	1PCS
1	TERMINALI HOUSING	HIGH TEMPERATURE PLASTIC	LCP BLACK/CONTACT: Au:1u"Min Ni base50u"Min	2PCS
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY

CUSTOMER DRAWING

铭创科技（东莞）有限公司
Mingchuang Technology (Dongguan) Co., Ltd.

UNITS: mm SCALE: 1:1 SHEET: 1 OF 3

PROJECTION: DRAW: DAP

GENERAL TOLERANCE: 0. ±0.25, 0.0 ±0.15, 0.00 ±0.05, 0.° ±1°, 0.0° ±0.5°

CHECK: HWT APPD: HHM

TITLE: TYPE C公头24PIN 立贴11.1 三脚立式 铆合

MAT'L: SEE TABLE FINISH: SEE TABLE

DWG. NO.: 0465.TCM.24LS.H5 PART NO.: SIZE: A4